



CTS SERIES: EVERYDAY ENCLOSED PERFORMANCE

The CTS Series delivers enclosed protection, secure storage, and confident towing in a clean, functional design. Built to handle tools, equipment, and personal gear, it's ready for everyday demands.

BUILD & STRUCTURE

HAT POST WALL FRAMING (24" OR 16" O.C.)

Steel hat posts reinforce the wall structure to reduce flex and support long-term durability. Spacing varies by capacity, with tighter 16" on-center framing on higher GVWR models for added strength.

ENGINEERED STRUCTURAL PANEL FLOORS & WALLS


3/4" floor and 3/8" wall panels provide a strong, stable structure that resists deformation and holds up to repeated use. Engineered for added moisture resistance, these panels offer more consistent performance than traditional wood products.

V-NOSE FRONT PROFILE

Improves towing stability and airflow while adding up to 18" of usable interior space.

16" DIAMOND PLATE STONE GUARD

Protects the front wall from road debris to help preserve finish and long-term appearance.



1-YEAR Limited Warranty
3-YEAR Structural Limited Warranty

KEY FEATURES

CURBSIDE DOOR WITH RV LOCK + CAM BAR LOCK

Dual-lock system adds security while maintaining smooth, reliable operation. Standard on most sizes, with select compact models offering it as an option.

LED LIGHTING

Bright, efficient LED lights enhance visibility for safer travel and deliver long-lasting performance. Sealed design helps protect against moisture and road debris.

RADIAL TIRES

Provide a smoother ride and more stable towing. Standard on most models, with select compact models equipped with bias-ply tires.



ENCLOSED CARGO TRAILERS
CTS SERIES



Available Exterior Colors



SPECIFICATIONS	CTS2K	CTS3K	CTS7K	CTS10K
Coupler	2"	2"	2-5/16"	2-5/16"
Wiring Connector	4-Way Flat	4-Way Flat	7-Way Round	7-Way Round
Tongue	3" x 2" Tube	5'-6" W: 3" x 2" Tube 7' W: 4" x 2" Tube	6" x 2" Tube	6" x 2" Tube
Frame	3" x 2" Tube	5'-6" W: 3" x 2" Tube 7' W: 4" x 2" Tube	6" x 2" Tube	6" x 2" Tube
Crossmembers O.C.	24"	24"	24"	16"
Roof Bows O.C.	24"	24"	24"	24"
Roof	Galvalume	Galvalume	Galvalume	Galvalume
Floor	3/4" ESP	3/4" ESP	3/4" ESP	3/4" ESP
Tie-Down Points	Optional	(4) 1K D-Rings	6'-7" W: (4) 1K D-Rings 8.5' W: (4) 5K D-Rings	(4) 5K D-Rings
Interior Height	44"	5' W: 61"; 6'-7" W: 79"	79"	79"
Walls	3/8" ESP	3/8" ESP	3/8" ESP	3/8" ESP
Wall Frame O.C.	24"	24"	24"	16"
Exterior	.024" Aluminum, Semi-Screwless, Bonded	.024" Aluminum, Semi-Screwless, Bonded	.024" Aluminum, Semi-Screwless, Bonded	.024" Aluminum, Semi-Screwless, Bonded
Sidewall Vents	N/A	Included	Included	Included
Suspension	Spring	Spring	Spring	Spring
Axle(s)	(1) 2,000 Lbs	(1) 3,500 Lbs, 4" Drop	(2) 3,500 Lbs, 4" Drop	(2) 5,000 Lbs, 4" Drop
Brake Axle(s)	N/A	N/A	Electric Brakes	Electric Brakes
Breakaway Kit	N/A	N/A	Included	Included
Tires	12" Bias 4.80X12	15" Radial ST205/75R15	15" Radial ST205/75R15	15" Radial ST205/75R15
Wheels	Black Mod, 5 on 4-1/2"	Black Mod, 5 on 4-1/2"	Black Mod, 5 on 4-1/2"	Black Mod, 5 on 4-1/2"
Fenders	Diamond Plate	Diamond Plate	6'-7" W: Diamond Plate 8.5' W: Smooth	Smooth
Interior Lights	(1) LED	(1) LED	(1) LED	(1) LED
Beavertail	N/A	N/A	Included on 20'+ L; All others N/A	Included on 20'+ L; All others N/A
Rear Door	Single Barn Door	Ramp w/ Extension	Ramp w/ Extension	Ramp w/ Extension
Curbside Door	N/A	36" W w/ RV and Cam Bar Latch (5X10: 32" W, 5X8: Option)	36" W Door w/ RV and Cam Bar Latch	36" W Door w/ RV and Cam Bar Latch



AVAILABLE SIZES & CAPACITY

SINGLE AXLE	4' x 6'
Item No.	4X6CTS2K
GVWR	2,000 Lbs.
Empty Weight	450 Lbs.
Payload Capacity	2,450 Lbs.
Overall W x L x H	59" x 109" x 68"
Interior W x L x H	41-1/2" x 84" x 48"
Rear Opening W x H	34" x 43"

SINGLE AXLE	5' x 8'	5' x 10'	6' x 10'	6' x 12'	7' x 12'
Item No.	5X8CTS3K	5X10CTS3K	6X10CTS3K	6X12CTS3K	7X12CTS3K
GVWR	2,990 Lbs.	2,990 Lbs.	2,990 Lbs.	2,990 Lbs.	2,990 Lbs.
Empty Weight	832 Lbs.	965 Lbs.	1,123 Lbs.	1,253 Lbs.	1,401 Lbs.
Payload Capacity	2,158 Lbs.	2,025 Lbs.	1,867 Lbs.	1,737 Lbs.	1,589 Lbs.
Overall W x L x H	79" x 131" x 78"	79" x 155" x 78"	91" x 168" x 103"	91" x 192" x 103"	102" x 192" x 103"
Interior W x L x H	57" x 110" x 60"	57" x 134" x 60"	68-1/2" x 134" x 79"	68-1/2" x 158" x 79"	79" x 158" x 79"
Rear Opening W x H	50" x 55"	50" x 55"	62" x 75"	62" x 75"	72" x 75"

TANDEM AXLE	6' x 12'	7' x 12'	7' x 14'	7' x 16'	8.5' x 16'	8.5' x 20'
Item No.	6X12CTS7K	7X12CTS7K	7X14CTS7K	7X16CTS7K	85X16CTS7K	85X20CTS7K
GVWR	7,000 Lbs.	7,000 Lbs.	7,000 Lbs.	7,000 Lbs.	7,000 Lbs.	7,000 Lbs.
Empty Weight	1,866 Lbs.	1,976 Lbs.	2,118 Lbs.	2,261 Lbs.	3,126 Lbs.	3,466 Lbs.
Payload Capacity	5,134 Lbs.	5,024 Lbs.	4,882 Lbs.	4,739 Lbs.	3,874 Lbs.	3,534 Lbs.
Overall W x L x H	91" x 192" x 103"	102" x 192" x 103"	102" x 216" x 103"	102" x 246" x 103"	102" x 246" x 103"	102" x 292" x 103"
Interior W x L x H	68-1/2" x 158" x 79"	79" x 158" x 79"	79" x 182" x 79"	79" x 206" x 79"	96"/82" x 205" x 79"	96"/82" x 253" x 79"
Rear Opening W x H	62" x 75"	72" x 75"	72" x 75"	72" x 75"	90" x 75"	90" x 75"

TANDEM AXLE	8.5' x 16'	8.5' x 20'	8.5' x 24'
Item No.	85X16CTS10K	85X20CTS10K	85X24CTS10K
GVWR	9,990 Lbs.	9,990 Lbs.	9,990 Lbs.
Empty Weight	3,126 Lbs.	3,466 Lbs.	3,742 Lbs.
Payload Capacity	6,864 Lbs.	6,524 Lbs.	6,248 Lbs.
Overall W x L x H	102" x 246" x 103"	102" x 292" x 103"	102" x 342" x 103"
Interior W x L x H	96"/82" x 205" x 79"	96"/82" x 253" x 79"	96"/82" x 301" x 79"
Rear Opening W x H	90" x 75"	90" x 75"	90" x 75"