



UTILITY TRAILERS: BUILT FOR EVERYDAY WORK

Designed for real-world use, these trailers deliver the strength, stability, and straightforward functionality needed to handle daily demands. Whether for personal projects or professional use, they're built to keep you moving.

CONSTRUCTION

2" SQUARE TUBE TOP RAIL

Reinforces the trailer sides to reduce flex under load, helping maintain stability and long-term structural integrity.

POWERSPINE™

Reinforced center rail conceals and protects wiring while adding strength and rigidity to the frame.

STEEL ANGLE FRAME

Forms a strong, dependable foundation that holds up under repeated use and helps keep the trailer tracking straight.

3,500 LB AXLES

Provide the capacity and balance needed for smooth, controlled towing whether empty or loaded.

TREATED WOOD FLOOR

Provides a durable, long-lasting deck surface that stands up to repeated use and exposure to the elements

KEY FEATURES

5K SET-BACK JACK

Provides stable front-end support while the set-back design improves clearance during transport and ease of use when hooking up.

VERSATILE GATE DESIGN + SPRING ASSIST

Functions as a ramp for easy loading or folds into the trailer bed to accommodate larger cargo. Spring assist reduces lifting effort for easier operation.

BULLDOG-STYLE COUPLER

Heavy-duty, secure connection designed for dependable towing and long-term durability

LED LIGHTING

Bright, efficient LED lights improve visibility and deliver long-lasting, low-maintenance performance.

SINGLE AND TANDEM AXLE
UTILITY TRAILERS



SPECIFICATIONS	UD3K (Single Axle)	UD7K (Tandem Axle)
GVWR	2,990 Lbs.	7,000 Lbs.
Available Sizes	6' Wide: 10', 12', 14' 7' Wide: 12', 14'	6' Wide: 12', 14', 16' 7' Wide: 14', 16', 18'
Paint Process	Painted Finish (Wet Spray)	Painted Finish (Wet Spray)
Coupler	2" Bulldog-Style	2-5/16" Bulldog-Style
Wiring Harness	4-Way Flat, Sealed Harness	7-Way Round, Sealed Harness
Tongue	4" Steel Channel A-Frame	4" Steel Channel A-Frame
Tongue Storage	Mesh Basket	Mesh Basket
Safety Chains	Class II, GVWR 3,500 Lbs., 30" x 1/4" w/ Hooks	Class IV, GVWR 7,600 Lbs., 30" x 5/16" w/ Hooks
Jack	5,000 Lbs. Drop-Leg, Top-Wind	5,000 Lbs. Drop-Leg, Top-Wind
Breakaway System	N/A	Electric Kit w/ Battery Charger
Axle(s)	(1) 3,500 Lbs.	(2) 3,500 Lbs. w/ Brakes
Frame	3" x 2" x 3/16" Steel Angle	3" x 2" x 3/16" Steel Angle or 4" x 3" x 1/4" Steel Angle
Uprights	14" H, 2" x 2" Steel Angle	14" H, 2" x 2" Steel Angle
Sides	Open	Open
Top Rail	2" Square Steel Tube	2" Square Steel Tube
Cargo Hold	Stake Pockets	Stake Pockets
Fenders	Steel	Steel
Tire & Wheel	15" Radial ST205/75R15, Black Steel Mod	15" Radial ST205/75R15, Black Steel Mod
Suspension	3-Leaf Spring, Double Eye	3-Leaf Spring, Double Eye
Ramp Gate	Fold-Down or -In w/ Spring Assist	Fold-Down or -In w/ Spring Assist
Rear Latch	Heavy-Duty Spring Latch	Heavy-Duty Spring Latch
Lights	LED	LED

